

TURBO-PRO 15W-40 CH-4

Heavy-duty Diesel Engine Oil

Product Description

Veedol Turbo Pro 15W-40 CH-4 is a heavy-duty diesel engine oil formulated with performance additives to deliver superior performance in engines.

The synthetic blend with balanced performance additives helps maintain viscosity for longer duration providing extended drain capability. It offers superior protection against wear, deposits, and maintains engine cleanliness.

Performance Specifications:

Veedol Turbo-Pro 15W-40 CH-4 meets & exceeds the performance requirements of

- API CH-4/SJ
- Cummins CES 20076
- MB 228.1
- Deutz DQC II-08
- MAN 3275
- Mack EOM-Plus

Application:

- Heavy-duty diesel vehicles conforming to BS III / Euro III and prior emission norms.
- Turbocharged and naturally aspirated diesel engines of all major engine manufacturers.
- Recommended oil drain interval 36,000Km*.

Features/Benefits:

- **Superior protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Superior soot control:** Special detergent additives prevent soot buildup in the engine, thereby preventing soot-induced thickening and ensuring efficient lubrication.
- **Improved engine cleanliness:** Superior resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8640
Kinematic Viscosity @ 40°C	cSt	D 445	103.5
Kinematic Viscosity @ 100°C	cSt	D 445	14.30
Viscosity Index		D 2270	141
Flash Point	°C	D 92	242
Pour Point	°C	D 927	-30
Total Base Number	mgKOH/g	D 2896	7.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED

[formerly Tide Water Oil Co. (India) Limited]

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

www.veedolindia.com