

## RUSPRO DW P02

*Soft Film Dewatering type Rust preventive oil*

### **Product Description:**

Veedol Ruspro DW P02 is a high-performance solvent-deposited, water displacing and non-staining type corrosion preventive. The product on evaporation leaves a thin, glossy, oily film on the component which ensures maximum protection in severe conditions.

Veedol provides effective protection against corrosion during short term storage. Dewatering action is most effective if the articles to be protected can be immersed in a dip tank. It can be removed by industrial solvents and aqueous neutral cleaners

### **Features/Benefits:**

- After Moisture removal Ruspro DW P02 leaves behind a thin oily protective rust inhibiting layer.
- It is formulated using excellent anti-corrosive additives.
- Good dewatering properties avoid entrapment of water which could lead to corrosion
- It provides excellent protection for ferrous and alloy components even in severe conditions.
- Once the machined component is applied with Veedol Ruspro DW P02, immediate action of protective film formation starts, and rest of the care is taken by this rust preventive layer.
- Indoor Properties - In ordinary industrial atmosphere, the treated components will remain rust free for 2 Months
- Easily removable with neutral cleaners.

### **Application:**

- Developed to use as a rust preventive oil for auto components and auto ancillary.
- Can be use as intermediate protection for removal of soluble oil emulsion.
- Use for protection of valuable machine tools during storage.
- Protection period: -Indoor storage: - 2 month, Outdoor storage: - 1 month.
- Can be applied either by dip / spray / or brush method.

### **Typical Properties:**

Characteristics	Typical value
Appearance	Clear, Amber Liquid
Film Coverage, sq. mt. / ltr	70
Film Thickness, microns	2 to 3
Salt Spray Characteristics, hours (ASTM B 117)	>24
Flash Point, °C (ASTM D 92)	>40
Water Displacement Test (De-Watering)	Passes
Protection – Indoors	2 months
Protection – Outdoors	1 months



#### **STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### **HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.