

RUSPRO DW 05

Soft Film Dewatering type Rust preventive oil

Product Description:

Veedol Ruspro DW P05 is a high-quality solvent-deposited, water displacing and non-staining type medium term corrosion preventive. The product on evaporation leaves a thin, glossy, oily film on the component which ensures maximum protection in severe conditions.

Veedol provides effective protection against corrosion during medium term storage. Dewatering action is most effective if the articles to be protected can be immersed in a dip tank. It can be removed by industrial solvents and aqueous neutral cleaners

Features/Benefits:

- After Moisture removal Ruspro DW P05 leaves behind a thin oily protective rust inhibiting layer.
- It is formulated using excellent anti-corrosive additives.
- Good dewatering properties avoid entrapment of water which could lead to corrosion
- Act as a fingerprint neutralizer.
- Free of heavy metals and economical to use.
- Easily removable with neutral cleaners.
- It provides excellent protection for ferrous and alloy components even in severe conditions.
- Indoor Properties - In ordinary industrial atmosphere, the treated components will remain rust free for 5 Months

Application:

- Developed to use as a rust preventive oil for auto components and auto ancillary.
- Can be use as intermediate protection for removal of soluble oil emulsion.
- Use for protection of valuable machine tools during storage.
- Protection period: -Indoor storage: - 5 month, Outdoor storage: - 3 month.
- Can be applied either by dip / spray / or brush method.

Typical Properties:

| Characteristics | Typical value |
|--|---------------------|
| Appearance | Clear, Amber Liquid |
| Film Coverage, sq. mt. / ltr | 80 |
| Film Thickness, microns | 2 to 4 |
| Humidity Cabinet Test, Hours (ASTM D 1748) | 720 |
| Salt Spray Characteristics, hours (ASTM B 117) | >72 |
| Flash Point, °C (ASTM D 92) | >40 |
| Water Displacement Test (De-Watering) | Passes |
| Protection – Indoors | 5 months |
| Protection – Outdoors | 3 months |



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.