HDC+

Diesel Engine Oil

Product Description

Veedol HDC+ is a top-up booster formulated with high-performance additives to enhance engine performance. Compatible with all viscosity grades, it is ideal for topping up diesel vehicles meeting BS IV and earlier emission standards. It delivers superior wear protection, enhanced oxidation stability, and excellent deposit control.

Applications:

Formulated as a universal top-up oil for pre-BS VI (BS IV and prior) naturally aspirated or turbocharged diesel engines operating across the following segments:

- Commercial Vehicles: Heavy-duty trucks, tippers, LCVs, SCVs and buses meeting BS IV/Euro IV or earlier emission norms.
- Off-Highway & Industrial Equipment: Excavators, backhoe loaders, bulldozers, graders, dumpers, stationary diesel generator (DG) sets, and captive industrial engines meeting CEV Stage IV or earlier emission norms.
- Agricultural Machinery: Tractors, combine harvesters, power tillers, and pump sets meeting TREM Stage IV or earlier emission norms.

Features & Benefits:

- Superior wear protection to extend engine life
- Outstanding engine cleanliness and sludge control
- Enhanced oxidation stability under high operating temperatures
- Improved soot handling capabilities

STORAGE
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH, SAFETY AND ENVIRONMENT
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED
Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.
Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.
www.veedolindia.com

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical Results
Density @ 29.5 °C	g/cm^3	ASTM D 4052	0.8620
Kinematic Viscosity @ 40 °C	cSt	ASTM D 445	109.5
Kinematic Viscosity @ 100 °C	cSt	ASTM D 445	14.6
Viscosity Index	-	ASTM D 2270	137
Flash Point	°C	ASTM D 92	230

The typical properties listed above are within normal production tolerances and do not constitute a specification. Variations that do not affect product performance may occur during normal manufacturing and across different blending locations. The information contained herein is subject to change without notice.

**Performance under standard test conditions.*

STORAGE
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH, SAFETY AND ENVIRONMENT
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED
Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.
Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.
www.veedolindia.com