



## Veedol OB 2T

### Premium 2-Stroke Outboard Engine Oil

#### Product Description:

Veedol OB 2T is a high performance, two-stroke engine oil developed specially for high performance, water-cooled two-stroke engines used in outboard marine applications.

Veedol OB 2T is formulated with high quality base oils and special additives providing exceptional overall engine cleanliness, reduced spark plug fouling and protection against rusting.

#### Performance Specifications:

Veedol OB 2T meets and exceeds below performances

- JASO FC
- API TC
- ISO-L-EGC
- TISI 1040-2534
- BIS T-SL4

#### Application:

- Recommended for use in modern high-performance, water-cooled, two-stroke engines, as well as smaller or older outboard engines. for all new generation 2-stroke motorcycles, scooters and auto-rickshaws.

#### Features/Benefits:

- Unique detergent additive system helps to remove carbon deposits from the engine surface.
- Provides excellent lubricity.
- Easy miscibility with fuel.
- Reduces exhaust port blockage, emits low smoke and facilitates easy start.

#### Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Kinematic Viscosity @ 100°C	cSt	D 445	9.500
Viscosity Index		D 2270	110
Flash Point	°C	D 92	124

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.



**Veedol**

**POWERING EFFICIENCY**

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



#### **STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### **HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

**VEEDOL CORPORATION LIMITED**

*[formerly Tide Water Oil Co. (India) Limited]*

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

[www.veedolindia.com](http://www.veedolindia.com)