

## **Veedol POWERTRON 15W-40**

### **Premium Synthetic Diesel Engine Oil**

#### **Product Description:**

Veedol Powertron 15W-40 is a premium quality fully synthetic diesel engine oil with advanced engine care technology specially developed for modern generation passenger cars and SUV's.

Veedol Powertron 15W-40 is formulated with latest technology additive system, providing highest level of engine protection.

#### **Performance Specifications:**

Veedol POWERTRON 15W-40 meets and exceeds below performances

- API CH-4

#### **Application:**

- Recommended for use in diesel engines of high performance passenger car and SUV's requiring API CH-4 specification oil.

#### **Features/Benefits:**

- Excellent protection against the build-up of piston deposits.
- Outstanding wear protection in all operating conditions.
- Exceptional oxidation stability protects against the formation of varnish at elevated temperatures.
- Excellent corrosion protection for reduced maintenance cost and longer engine life.
- Improved engine durability.



#### **STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### **HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

**Typical Properties:**

Test Parameters	Unit	ASTM Test Method	Typical results
Appearance	-	Visual	Clear & Bright
Kinematic Viscosity @ 100°C	cSt	D 445	14.7
Viscosity Index		D 2270	138
Total Base Number	mgKOH/g	D 2896	8.35
Pour Point	°C	D 97	-27
Flash Point	°C	D 92	238

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.